

PRODUCT SPECIFICATION – Multi Sensor Weather Station II



Features: One Multi Sensor supports more products from the JACOB JENSEN™ Weather Station II series, among others: JACOB JENSEN™ Thermometer II Silver Version and JACOB JENSEN™ Hygrometer II Silver Version. Up to three sensors can be connected. No wiring is required between the sensor(s) and the product(s). Number of channels: 3 Transmission range: 100 m unobstructed. **-2**0°C to 60° C Temperature range: **Humidity range:** 25% - 95% relative humidity **Humidity resolution:** 0.1°C / 1% relative humidity Frequency: 868 MHz. Front view: RΠ Indicates AM/PM (only in UK time mode). î Radio controlled clock reception icon. [2] Indicates which channel has been set. Indication for low battery. 15:38 Clock. **25**.5t / **B5**.6 Temperature / humidity. Back view: Reset the unit to the default settings. 0 Disable / enable the radio control signal. 0 °C / °F button (EU version: °C / US version: °F) ≅⊞≚ EU / UK switch (for the radio controlled clock). Channel switch. Note at first time set-up with main unit: Data transmission will align automatically when the main unit is turned on for the first time or after replacement of batteries. The main unit receives a signal every minute. If the signal cannot be received, "LOST LINK" will appear on the main unit, and the receiving time will increase in steps until the signal is reconnected. If the signal cannot be picked up (within 12 hours), "LOST LINK" remains on the main unit and both the sensor and the main unit must be RESET in order to re-establish the connection. 1 x UM-3 (AA) 1.5 V battery. Battery: Weight: 135 g without battery. Dimensions: W 69,5 x H 135 x D 25 mm Material: ABS, PMMA and silicone.