## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

<b>Supplier's name or trade mark:</b> UMAGE	
---	--

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2437 (light-source)

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	<b>3</b> Uui C	c.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Custom LED PCB		
(or other electric interface)	20,2V DC 550mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Parameter		Value	Parameter	Value
General product parameters:				
Energy consur mode (kWh/10 up to the neares	00 h), rounded	12	Energy efficiency class	D
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	1 732 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 900
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	11,1	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00
	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84
Outer dimen-	Height	295	Spectral power dis-	See image
sions without	Width	295	tribution in the	in last page
separate con- trol gear, light-	Depth	2	range 250 nm to 800 nm, at full-load	

ing control parts and non- lighting con- trol parts, if any (millime- tre)				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,438	
		nates (x and y)	0,400	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	13	Survival factor	0,90	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

