## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2448 (light-source)

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIGIIL	source.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Custom LED PCB 40V DC 500mA MAX		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Darameter		Value	Daramatar	Value	
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	nption in on- 00 h), rounded st integer	21	Energy efficiency class	D	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 098 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700 or 3 000 or 4 000 or 6 000	
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	20,5	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
(P <sub>net</sub> ) for CLS, 6	candby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	96	
Outer dimen-	Height	30	Spectral power dis-	See image	
sions without	Width	975	tribution in the	in last page	
separate con-	Depth	1	1		

trol gear, lighting control parts and non-lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load		
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-	
		Chromaticity coordi-	0,373	
		nates (x and y)	0,369	
Parameters for LED and OLED light sources:				
R9 colour rendering index value	79	Survival factor	1,00	
the lumen maintenance factor	0,96			

(a)'-': not applicable; (b)'-': not applicable;

