## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: UMAGE

Supplier's address: UMAGE ApS, Havnegade 29, 1058 Copenhagen, DK

Model identifier: 2415 (light-source)

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	Custom LED PCB 20,3V DC 700mA		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with spe- cific dimmers

## **Product parameters**

Parameter		Value	Parameter	Value		
General product parameters:						
0,	nption in on- 00 h), rounded st integer	15	Energy efficiency class	D		
dicating if it refe a sphere (360°)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	2 166 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	2 900		
On-mode pow pressed in W	ver (P <sub>on</sub> ), ex-	14,2	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	84		
Outer dimen-	Height	354	Spectral power dis-	See image		
sions without	Width	354	tribution in the	in last page		
separate con- trol gear, light-	Depth	1	range 250 nm to 800 nm, at full-load			

ing control parts and non- lighting con- trol parts, if any (millime- tre) Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W) Chromaticity coordi-	- 0,440			
		nates (x and y)	0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	12	Survival factor	0,90			
the lumen maintenance factor	0,96					
$(\mathbf{a})$						

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

